

RESBOND™ 907TS THREADLOCKERS

Viscosities and Strengths To Meet Your Toughest Sealant Needs

Use From -300°F to 2100°F

It's easy ! No mixing required.

Just apply and let dry.

Resbond 907 TS cures at room temperature

Forms thermally Stable, electrically insulating,
Chemically Resistant Bonds.

Packaged in convenient 4 oz. applicator bottles.

Will not run off or drip while applying.

Ideal for use on set screws,
fasteners, bolts, pipes threads.

Removable with hand tools (under most conditions).



- **Easy to Use**
- **Economical**
- **Room Temp. Cures**
- **High Temp. Stability**
- **High Bond Strength**
- **Electrical Resistance**



No measuring. No mess. Will not run or drip.

Just one bottle provides up to 2000 applications!

Saves time and money. No costly heat treatments.

Will not soften or decompose at elevated temperatures.

Excellent Adhesion. Seals most metals and ceramic parts.

Penetrates fine openings to provide electrical resistance.

Resbond™ 907TS	Use For	Viscosity (cps)	Shear Strength (psi)	Breaking Torque (inch-lbs.)	Gap Fill (in.)	Applications Include
Green Low Viscosity	Penetrating Fine Openings	2,000	370	80	0.003	Small, Set, Adjustment Screws, Fasteners, and Instrumentation.
Blue Standard Loosening	Preventing Vibration	5,000	400	180	0.005	Large Fasteners and Set Screws, Pipe Threads, Bearings, etc.
Red High Strength	Filling Large Gap Widths	7,000	450	250	0.010	Studs, Nuts, Bolts, Large Fasteners, Pipe Threads, etc.
Gold High Viscosity	General Purpose	15,000	500	300	0.030	Medium Screws, Nuts, Bolts, Pipe Threads, and Fittings.

Cat. No.

Description

Cost

Distributed By:

907TS-1

4 oz. Applicator Bottles (Specify Green, Blue, Red or Gold)

Case Pack 12-4 oz. Applicator Bottles

907TS-TK

Trial Evaluation Kit (4- 1 oz. Applicator Bottles)



COTRONICS CORPORATION

www.cotronics.com

(718) 646-7996 Fax (718) 646-3028 3379 Shore Parkway, Brooklyn, N.Y. 11235